

soapwell
by **ELKAY**™



**COMPLETELY
HANDS-FREE**



**INSTANT
HOT WATER**



**EASY-TO-CLEAN
DESIGN**

MOBILE HANDS-FREE WASH STATION

NORTH AMERICA CATALOG

ELKAY / 100 YEARS

Elkay is a family-owned and operated company with over 100 years of manufacturing experience. Today, Elkay delivers world-class innovations for sinks, faucets, foodservice products, water coolers, drinking fountains, and bottle filling solutions.

Table of Contents

- Overview
- Products
- Accessories
- Replacement Parts
- Support



BRINGING HEALTH AND WELLNESS WHERE IT MATTERS

SOAPWELL™ IS A COMPLETELY **HANDS-FREE** WASH STATION THAT ADAPTS TO ANY ENVIRONMENT, ANYWHERE. WITH A **TOUCHLESS** SOAP, WATER, AND TOWEL DISPENSER, THIS **MOBILE** UNIT IS TRANSFORMING THE FUTURE OF CLEANLINESS.



100% HANDS-FREE

Completely touchless, the sensors activate the faucet, soap dispenser, and paper towel dispenser.

CLEANER ENVIRONMENTS

The durable stainless steel design is easy to disinfect, leaving you with a cleaner space and healthier customers and communities.

MOBILE

The portable unit is built on locking casters and features recessed pull handles, making it easy to reposition or relocate.

LESS WASTE

Removing hands automatically stops the delivery of water, soap, and paper towel – wasting less and saving you money.



INSTANT HOT WATER

Hot water at your fingertips. With an electric water heater and pump, the unit holds 25 liters of freshwater and 30 liters of wastewater.

SIMPLE INSTALLATION

Using 220-240V power with no plumbing required, this unit is simple to set up and easy to operate.

LET'S BUILD HEALTHIER COMMUNITIES TOGETHER.

Certified by NSF International - NSF/ANSI 169
*patent pending 
This product is UL Listed 

Soapwell™ Standard

PRODUCT SPECIFICATIONS

Elkay's self-contained, touchless handwashing station. Includes touchless electronic faucet, touchless soap, and touchless towel dispensers. On-demand water heater, 5-gallon freshwater tank, and 6-gallon wastewater tank conveniently contained within the mobile cabinet.

MODEL	MHS2424HF
FAUCET	ELKAY commercial electronic faucet model LKB737C, sensor activated with auto shut off
FLOW RATE	0.5 GPM
CABINET DIMENSIONS (L X W X H) (INCHES)	24" x 24" x 62"
HAND SINK	Stainless Steel 10" X 12" X 6" deep
WATER HEATER ELECTRICAL RATING	120 VAC 1500 Watts 20A Dedicated outlet
ON DEMAND HOT WATER	65 to 145 °F
MIXING VALVE	Manual mixing valve installed
FRESH WATER CAPACITY	5-Gallon removable plastic tank
WASTE WATER CAPACITY	6-Gallon removable plastic tank
SOAP DISPENSER *	Sensor activated, touchless operation, battery operated. Accepts 0.3gal bag refill cartridges
TOWEL DISPENSER*	Sensor activated, touchless operation, battery operated
STEEL TYPE	301 stainless steel construction
CERTIFICATIONS	CSA C22.2 No. 109, NSF 169, UL 197
FEATURES	Two locking and two non-locking 5-inch casters, handles for moving cabinet, and hinged door with locking latch for internal access



*patent pending

BENEFITS

01

Sanitary

All touchless. No need to make contact to activate soap, faucet, or towels. Stainless steel cabinet is hygienic, easy to clean, and sanitize.

02

Portable

Can be positioned anywhere handwashing is needed.

03

Durable

All welded stainless steel construction.

04

Certifications

Conforms to NSF construction and designed to meet state and local handwashing codes.

PRODUCT COMPLIANCE

CSA C22.2 No. 109, NSF 169, UL 197



CLEANING, CARE & INSTALLATION

For proper cleaning, care, and installation instructions, please visit our website at soapwellbyelkay.com.

* Make and model of touchless electronic faucet, towel dispenser, and soap dispenser may vary but will have the same functionality and warranty.

SOAPWELLBYELKAY.COM

Soapwell™ Direct Connect

PRODUCT SPECIFICATIONS

Elkay's self-contained, touchless hand washing station. Includes sensor activated electronic faucet, touchless soap, and towel dispensers. On-demand water heater can be connected to the water and drain line.

MODEL	MHS2424HF01
FAUCET	ELKAY commercial electronic faucet model LKB737C, sensor activated with auto shut off
FLOW RATE	0.5 GPM
CABINET DIMENSIONS (L X W X H) (INCHES)	24" x 24" x 62"
HAND SINK	Stainless Steel 10" X 12" X 6" deep
WATER HEATER ELECTRICAL RATING	120 VAC 1500 Watts 20A Dedicated outlet
ON DEMAND HOT WATER	65 to 145 °F
MIXING VALVE	Manual mixing valve installed
FRESH WATER CAPACITY	Requires ¾" Male Hose
WASTE WATER CAPACITY	Requires ¾" Female Hose
SOAP DISPENSER *	Sensor activated, touchless operation, battery operated. Accepts 0.3gal bag refill cartridges
TOWEL DISPENSER*	Sensor activated, touchless operation, battery operated
STEEL TYPE	301 stainless steel construction
CERTIFICATIONS	CSA C22.2 No. 109, NSF 2, UL 197
FEATURES	Direct connect to water and drain line. Two locking and two non-locking 5-inch casters, handles for moving cabinet, and hinged door with a locking latch for internal access



*patent pending

BENEFITS

01

Sanitary

All touchless. No need to make contact to activate soap, faucet, or towels. Stainless steel cabinet is hygienic, easy to clean, and sanitize.

02

Portable

Can be positioned anywhere handwashing is needed.

03

Durable

All welded stainless steel construction.

04

Certifications

Conforms to NSF construction and designed to meet state and local handwashing codes.

05

Internal Fresh Water Check Valve

Complies with NSF/ANSI 2 and ASSE1024

PRODUCT COMPLIANCE

CSA C22.2 No. 109, NSF 2, UL 197



CLEANING, CARE & INSTALLATION

For proper cleaning, care, and installation instructions, please visit our website at soapwellbyelkay.com.

* Make and model of touchless electronic faucet, towel dispenser, and soap dispenser may vary but will have the same functionality and warranty.

Soapwell™ Accessories - Covers

TECHNICAL DATA

100% Solution Dyed Polyester, 600 x 600 Denier

ROLL SIZE	100 yards
SCRIM COUNT	600 x 600
WEIGHT	7.5 oz.
WIDTH	60"
BACK COATING	Urethane Coating
FIBER TYPE	Solution dyed polyester
SUBSTRATE FABRIC TYPE	Polyester
BAG TEST	Pass
FLAME RETARDENCY	No
HYDROSTATIC	90 CM.
MILDEW RESISTANCE	Yes
SHRINKAGE	<1%
SPRAY RATING	100 Front and back
TENSILE STRENGTH	325 x 275
TONGUE TEAR	40 x 35
UV RESISTANCE	Yes
WATER REPELLENCY	Excellent



Part	Description	Type	Price
SCHFC-001	Soapwell Cabinet Hands-Free Cover Fabric: Surlast 600 x 600 Charcoal 6665-04	M	REQUEST A QUOTE

01 3 YEARS LIMITED WARRANTY

This limited warranty is valid only if a copy of the invoice for the item purchased is submitted showing the date of original purchase. This limited warranty is only valid for SurLast® that has been fabricated and Installed properly.

02 CARE

SurLast® is designed to be easy to care for. It can be washed or brushed off, and rinsed. Proper care and cleaning are important to the life of the fabrics. Please consult rochfordsupply.com for more cleaning information.

03 EASE OF USE

SurLast® helps save the manufacturer money because of its ease of use and flexibility. The urethane coating also makes it more water-resistant and adds dimensional stability.

The SurLast® coating allows the material to be used without having to allow for shrinkage or stretch. No hot knife surging is required to fabricate with SurLast®. For best results and lasting appearance, always sew your project with the fabric side exposed to the sun and the coated side protected from the sun.

This limited warranty covers the fabric becoming unserviceable because of loss of color or strength from normal usage and exposure conditions, including sunlight, mildew, and atmospheric chemicals. The consumer is responsible for normal care and cleaning of the fabric. The warranty covers fabric only. Rochford Supply's liability is expressly limited to this warranty.

Soapwell™ Replacement Parts

REPLACEMENT PARTS (For Models EHS2424HF and MHS2424HF)

Part Number	Replacement Part Description
LKB737C	Electronic Sensored Faucet
74160038	Pull Handle
CT-77	5" Plate Caster, Set, 2 Locking, 2 Non-Locking
74160438	8' Cord, 14 GA
74160354	5-Gallon Freshwater Jug, Blue
74160353	6-Gallon Grey Water Jug
1000005766	Mixing Valve
1000005860	GL 2.5 TI Hot Water Heater
1000005762	Flexible Tailpiece
74160356	1.7 GPM Diaphragm Pump W/6" Power Cord
1000005764	Braided Water Connector 3/8" X 1/2" X 12"
74160351	Hose 5/8" Round #410, 1 EA. 48" Long
1000005749	PVC with Spiraled Polyester Yarn 1/2" Braided Tubing, 1 EA. 28" Long

Request a quote for pricing!

WATER TANKS

Part Number	Description
741603545	Gallon Freshwater Jug, Blue
741603536	Gallon Grey Water Jug



UPGRADE KITS

Part Number	Description
1000005997	Includes Tubing and Fitting to Replace Internal Water Lines



Frequently Asked Questions

01

What does 100% touchless mean?

Sensors activate the faucet, soap, and paper towel dispensers. Removing hands automatically stops the delivery of water, soap, and paper towel.

02

How many washes can Soapwell handle per 5-gallon tank of freshwater?

- (46) washes per (5) gallon freshwater tank with the expectation:
- Faucet uses ½ gallon per minute
- 5 seconds to wet hands
- 20 seconds washing hands (no water in use)
- 10 seconds to rinse hand

03

Hot water is listed as 65-145 F. Is there a manual setting to specify it?

The heater can be manually adjusted between 65 and 145° F. There is a desired setting marked on the heater. The mixing valve will temper and maintain the water temperature at the desired setting.

04

What type of soap dispenser will my Soapwell unit come with?

Staple's Coastwide Professional J-Series automatic soap dispenser; Soapwell will utilize the citrus antibacterial soap, but the dispenser can be refilled using any of the Coastwide Professional J-Series foam soap refills. Soapwell will come with (2) soap refills and reorder information will be provided with the product.

05

What type of towel dispenser will my Soapwell unit come with?

Staple's Coastwide Professional J-Series automatic towel dispenser; Soapwell will utilize the "natural" Hardwound Towel Roll, but the dispenser can be refilled using any of the Coastwide Professional J-Series Hardwound Towel Rolls. Soapwell will come with (2) towel refills and reorder information will be provided with the product.

06

Will soap and paper towels be provided with my Soapwell unit?

Each Soapwell unit is shipped with a small supply of soap and paper towels to get you started. Please refer to the information packet that arrived with your Soapwell for details on ordering soap and paper towels for your unit.

Have more questions?

Get in touch with our Customer Support Team for assistance.

Contact us at **800-726-0553** or **CommercialSalesSupport@elkay.com**.

Additional Safety Products



MOBILE SERVING CARTS

Keeping a safe distance can be a challenge for those who need to contact others, especially food service employees. Our mobile serving carts are designed for more accessible transportation, safer storage, easy to disinfect surfaces, and 6' distancing with an acrylic screen for added safeguarding.



ACRYLIC PARTITION SCREEN

Provide an additional layer of protection in restaurants, businesses, and schools with our acrylic partition screens. Our divider screens are crafted with the highest quality materials, leaving you with a quality safety solution that can be easily moved wherever it's needed.



DESK DIVIDER SCREEN

Keep students and staff safe with transparent desk divider screens. Acrylic barriers are a great way to add protection in the classroom without hindering the learning experience and allowing for that needed social connection between classmates.



SHELF B CART

The Shelf B Cart features a powder-coated tubular steel frame, metal mesh dividers, and a fixed shelf. Casters allow the cart to be wheeled from space to space. The cart is intended to be a simple food transport that holds insulated bags for meal selections while limited the spread of germs.



Anywhere, Any Environment

Soapwell offers an easy way to stop the spread of germs by simply washing your hands. From businesses, retail, or education, to sports arenas and concert venues, Elkay's mobile unit offers the flexibility and innovation to cater to any setting.

LEARN MORE AND START YOUR QUOTE.

SOAPWELLBYELKAY.COM
+1.800.726.0553

SOAPWELLBYELKAY.COM
EKCMHFWSNA-2001
v.040121